



GraeL PSG

grael psg

Industry-leading amplifier optimized for Gold Standard HD PSG studies.

Over 25 years of experience in designing PSG and EEG amplifiers, including the highly successful E-Series, has culminated in GraeL PSG. Based on the flagship GraeL amplifier, the GraeL PSG has a channel subset dedicated for Sleep studies. A true-HD PSG amplifier with channels as specified for the Gold standard AASM Type 1 studies.

HD PSG

Technical specifications



DIMENSIONS

Grael System Component	Size L x W x H	Weight
Amplifier	240mm x 144mm x 50mm 9.45in x 5.66in x 1.97in	700 grams 24.7 ounces

NETWORK

POE (power over Ethernet)

NETWORK CONNECTION

Drop in cradle for quick disconnect

ANALOGUE TO DIGITAL CONVERTER

24 bit resolution

DATA SAVE RATE

256, 512, 1024, 2048 sps

SAMPLE RATE

16384 sps

PATIENT CONNECTIONS

CF as per IEC60601-1

SAFETY

IEC60601-1

EMC

IEC60601-1-2

COMMUNICATION INTERFACE

Network Type 802.3/802.3u twisted pair
Ethernet with auto MDIX
Supports IPV4 with DHCP, TCP, UDP,
ICMP and ARP protocols

13 REFERENTIAL CHANNELS

Range $\pm 300\text{mV}$ (resolution $< 50\text{nV}$)
Frequency response DC to 580 Hz (user adjustable)
Input impedance $> 100\text{M}$
CMRR $> 100\text{dB}$
Noise (0.1 to 70Hz) $2\mu\text{Vpp}$ typical

6 DIFFERENTIAL CHANNELS

Range $\pm 300\text{mV}$ (resolution $< 50\text{nV}$)
Frequency response DC to 580 Hz (user adjustable)
Input impedance $> 20\text{M}$
CMRR $> 100\text{dB}$
Noise (0.1 to 70Hz) $2\mu\text{Vpp}$ typical

2 RESPIRATORY INDUCTIVE PLETHYSMOGRAPHY CHANNELS

Sensor Inductive band
Frequency response DC to 64 Hz

PRESSURE

Differential input 2 male luer
Range $\pm 100\text{cmH}_2\text{O}$
Frequency response DC to 580 Hz (user adjustable)
Accuracy $\pm 1\text{cmH}_2\text{O}$ at 25°C

POSITION

Sensor Tri-axial accelerometer
Positions Supine, prone, left, right, upright

MICROPHONE

Sensor Electret
Frequency response 5 to 580 Hz (user adjustable)

LIGHT

Sensor Integrated

OXIMETER

SPO₂ range 25 to 100%
Heart rate range 18 to 300 pulses per minute
SPO₂ accuracy 70 – 100% ± 2.5 digits within
1 standard deviation
Heart rate accuracy $\pm 1\%$ ± 1 digit

Sample rate

(SPO₂, HR, status) 1 sample per second, up sampled
to match the other channels

Sample rate

(plethysmograph) 256 samples per second, up sampled
to match the other channels

ENVIRONMENTAL REQUIREMENTS

Temperature Ambient operating temperature range:
 $0^\circ\text{C} - 40^\circ\text{C}$ ($32^\circ\text{F} - 104^\circ\text{F}$)
Storage temperature range:
 $-10^\circ\text{C} - 50^\circ\text{C}$ ($-4^\circ\text{F} - 122^\circ\text{F}$)

Humidity

20% - 90%-relative humidity
(non-condensing)

Altitude

Less than 3,000m

ELECTRICAL SPECIFICATIONS

Power Supply

All power provided by the network
connection using Power Over Ethernet
(either mid-span injector or POE Switch,
per IEEE 802.3af standard)

Operating voltage 48 volts

Power consumption < 10 watts

For more information please contact:

Compumedics Limited, Australia:

Headquarters
30-40 Flockhart Street
Abbotsford VIC 3067, Australia
Ph: +61 3 8420 7300
Fax: +61 3 8420 7399
Free Call: 1800 651 751

Compumedics USA, Inc.:

5015 West WT Harris Blvd, Suite E
Charlotte, NC 28269
Toll Free: +1 877 717 3975
Ph: +1 704 749 3200
Fax: +1 704 749 3299

Compumedics Europe GmbH:

Werdauer Strasse 1 - 3
01069 Dresden
Ph: +49 351 5019-7682
Fax: +49 351 5019-7684

Compumedics France SAS:

Rue Jean Sapidus,
Bât Pythagore
67400 Illkirch-Graffenstaden
Ph: +33(0) 981 062 869
Fax: +33(0) 970 604 963



All specifications are subject to change without notice.
Please contact your Compumedics representative for
latest technical information, pricing and product
availability. Grael, COMPUMEDICS and the Compumedics
logo are registered trademarks of Compumedics.



www.compumedics.com